


**Vorläufige
Werknorm**

Product-group
Koax 75 Ω
CC-Koax cable



Part.-No.16052 02X

Koax cable 75Ω, flexible cable blue

CONSTRUCTION

Core	Staku silver-coated
Core insulation	FEP (6Y)
Core diameter	1,52mm
Shield	aluminium foil
Shield	Copper-braid tin-plated, optical covering $\geq 85\%$
Inner-sheath	PP (9Y)
Outer-sheath	Special-TPE
Sheath colour	blue (RAL 5011)
Outer-diameter	4,3±0,2mm
Printing	RG 75 Ohm CE MM/JJ

TECHNICAL DATA

Rated voltage	500V
Test voltage	1,5kV
Insulation resistance	$\geq 1.000M\Omega \times km$
Impedanc	75Ω
Temperatur range	fixed installation -40°C up to +90°C flexible installation -25°C up to +90°C
Bending radius	fixed installation 7,5 x outer-diameter flexible installation 15 x outer-diameter
Copper weight	10,5kg/km
Weight	15,2kg/km

STANDARDS

RoHS II	conform
---------	---------

Datei: 1\Datenblaetter\WORLAEUFIG\100-199\16052016_e.doc

Erstellt	Geprüft	Änderungsstand	Änderung geprüft	Dieses Datenblatt darf ohne unsere ausdrückliche Genehmigung weder vervielfältigt, noch an dritte Personen oder Konkurrenz-Firmen im Original oder als Kopie ausgehändigt werden. Eigentum – und Urheberrecht vorbehalten.	Art.Nr. angelegt
Datum: 20.01.2017	Datum: 20.01.2017	Datum:	Datum:		Datum:
Name: tkü	Name: [Signature]	Version:	Name:		Name: