

CC-Lift-H-180

电梯电缆，带麻绳支撑和编织物加固

ConCab kabel gmbh



应用领域

CC-Lift-H-180 主要用于电梯、升降机构以及输送带装置中。额外包覆电缆的纺织编织带确保了其在运转中弯曲时不会磨损芯线，保护芯线免受外部机械拉力。

application

The CC-lift-H-180 is specially designed to be used in lift, elevator constructions and in conveyor installations. The additional textile braid covering the cable assembly ensures flexing work during running does not impinge on the cores so that the cores are protected from exterior mechanical strains.

构造

超细裸铜丝多股精绞成束，PVC 芯线绝缘，黑色芯线连续白色数字编号并且带绿黄保护接地导线。芯线包裹麻绳绞合节距短，编织带包覆，编织物加强。外护套特殊 PVC 材料，耐候性好，阻燃和自熄（符合 DIN EN 60332-1-2 VDE 0482 第 332-1-2:2005-06 部分标准）。外护套颜色为黑色。

construction

Superfine strands of bare copper wire, PVC core insulation, core colours black with white numbering and greenyellow protective conductor on the outer layer. Cores twisted in very short lay lengths around the hemp element, textile tape wrapping, textile braid. Outer sheath based on cold-flexible PVC, weather resistant, flame retardant and self extinguishing (acc. to DIN EN 60332-1-2 VDE 0482 part 332-1-2:2005-06). Colour black.

技术数据 / technical data

额定电压 / rated voltage:

300/500 V

测试电压 / test voltage:

3.000 V

导体绞合方式 / conductor stranding:

超细铜丝绞合 / super fine copper strands,

符合 / acc. to DIN VDE 0295, 6 类标准 / class 6 min. 20 MOhm x km

绝缘阻抗 / insulation resistance:

温度范围 / temperature range:

移动应用 / flexible application: -15° C 至 /to +70° C

弯曲半径 / bending radius:

移动应用 / flexible application: 20 x d 外径 -Ø / outer-Ø

符合标准 / approvals:


符合 / acc. to

DIN VDE 0250, 0285

Robust-Ltg.
Schleppflex®
BUS-Ltg.
Steuer-Ltg.
Daten-Ltg.
IT/Kommunik.
Hochtemp.-Ltg.
Aufzugs-Ltg.
Gummi-Ltg.
Einzel-Adern
Spiralkabel
Kabel-Zubehör
Technik-Anhang

CC-lift-H-180

lift cable with hemp support and braided fabric



物料编码 part-no.	芯线数 / 导体截面积 no. of cores / cross-sections	铜重 copper weight kg/km	外径 outer-Ø d mm	电缆重量 weight kg/km	悬挂长度 suspension length m
180 0007 012	12 G 0,75	86	18,0	370	120
180 0007 018	18 G 0,75	130	18,4	465	120
180 0007 024	24 G 0,75	173	20,8	520	80
180 0010 007	7 G 1,0	67	14,7	230	90
180 0010 012	12 G 1,0	115	18,8	400	80
180 0010 018	18 G 1,0	173	19,5	450	80
180 0010 020	20 G 1,0	192	20,0	500	70
180 0010 024	24 G 1,0	230	22,3	590	60
180 0010 036	36 G 1,0	346	28,0	950	90
180 2810 205	28 G 1,0 + (2x 0,5)	295	25,9	765	90

robust cables
Schleppflex®
BUS cables
control cables
data cables
IT/communic.
high-temp.
lift cables
rubber cables
single cores
spiral cables
accessories
technical annex