

CC-power cable NYY-O-804

0,6/1kV

ConCab kabel gmbh



应用领域

CC-power cable-NYY-O-804 主要用于供电网络的铺设，也可在干燥或潮湿的室内使用，以及砖块和混凝土中使用，但是这款电缆不能被摇动，震动或在受压力被压缩的混凝土中使用。该电缆可以铺设在水中和地下。该电缆在紫外线辐射中稳定。

application

The CC-power cable NYY-O-804 is designed to be laid in power supply networks over, on, inside and under plaster in dry, damp and wet rooms as well as in brickwork and in concrete with the exception of cabling in shaken, vibrated and compressed concrete. This cable is suitable to be laid in water and underground. It is stable to UV radiation.

构造

裸铜丝实心或多芯铜丝绞合，PVC 芯线绝缘，芯线颜色符合 DIN VDE 0293 308 部分标准，芯线绞合成缆。PVC 外护套，阻燃和自熄（符合 DIN EN 60332-1-2 VDE 0482 332-1-2:2005-06 部分标准）。外护套颜色为黑色。

construction

Bare, solid or multiple strands of copper, PVC core insulation, core colours acc. to DIN VDE 0293 part 308, cores twisted in layers. PVC outer sheath, flame retardant and self-extinguishing (acc. to DIN EN 60332-1-2 VDE 0482 part 332-1-2:2005-06). Colour black.

技术数据 / technical data

额定电压 / rated voltage:

0,6/1kV

测试电压 / test voltage:

4000 V

导体绞合方式 / conductor stranding:

实心或多芯铜丝绞合 /

solid or multiple copper strands,

符合 / acc. to DIN VDE 0295, 1 类或 2 类标准 / class 1 or 2 min. 100 MOhm x km

绝缘阻抗 / insulation resistance:

温度范围 / temperature range:

固定安装 / fixed installation: -40° C 至 /to +70° C

弯曲半径 / bending radius:

固定安装 / fixed installation: 12 x d 外径 -Ø / outer-Ø

符合标准 / approvals:

符合 / acc. to DIN VDE 0276-603

Robust-Ltg.

Schleppflex®

BUS-Ltg.

Steuer-Ltg.

Daten-Ltg.

IT/Kommunik.

Hochtemp.-Ltg.

Aufzugs-Ltg.

Gummi-Ltg.

Einzel-Adern


Spiralkabel

Kabel-Zubehör

Technik-Anhang

CC-power cable NYY-O-804

0,6/1kV



ConCab kabel gmbh

物料编码 part-no.	芯线数 / 导体截面积 no. of cores / cross-section	铜重 copper weight kg/km	外径 outer-Ø d mm	电缆重量 weight kg/km
804 0015 002	2 x 1,5 RE	29	12,0	180
804 0015 003	3 x 1,5 RE	43	12,0	200
804 0015 004	4 x 1,5 RE	60	13,0	240
804 0015 005	5 x 1,5 RE	72	14,0	270
804 0015 007	7 x 1,5 RE	101	15,0	360
804 0025 002	2 x 2,5 RE	48	12,0	250
804 0025 003	3 x 2,5 RE	72	13,0	265
804 0025 004	4 x 2,5 RE	98	14,0	295
804 0025 005	5 x 2,5 RE	120	15,0	360
804 0040 001	1 x 4 RE	38	8,0	120
804 0040 002	2 x 4 RE	77	15,0	325
804 0040 003	3 x 4 RE	115	15,0	360
804 0040 004	4 x 4 RE	154	17,0	480
804 0060 001	1 x 6 RE	58	9,0	155
804 0060 002	2 x 6 RE	115	15,0	400
804 0060 003	3 x 6 RE	174	16,0	435
804 0060 004	4 x 6 RE	230	18,0	590
804 0100 001	1 x 10 RE	96	10,0	190
804 0100 002	2 x 10 RE	192	17,0	485
804 0100 003	3 x 10 RE	288	18,0	560
804 0100 004	4 x 10 RE	384	20,0	790
804 0160 001	1 x 16 RE	154	10,0	260
804 0160 002	2 x 16 RE	307	19,0	750
804 0160 003	3 x 16 RE	462	20,0	820
804 0160 004	4 x 16 RE	614	22,0	1.100
804 0250 001	1 x 25 RM	240	13,0	380
804 0250 002	2 x 25 RM	480	24,0	1.150
804 0250 004	4 x 25 RM	960	27,0	1.650

物料编码 part-no.	芯线数 / 导体截面积 no. of cores / cross-section	铜重 copper weight kg/km	外径 outer-Ø d mm	电缆重量 weight kg/km
804 0350 001	1 x 35 RM	336	14,0	490
804 0350 004	4 x 35 RM	1.344	30,0	2.160
804 0500 001	1 x 50 RM	480	15,0	650
804 0500 004	4 x 50 SM	1.920	30,0	2.350
804 0700 001	1 x 70 RM	672	16,0	860
804 0700 004	4 x 70 SM	2.688	33,0	3.250
804 0950 001	1 x 95 RM	912	19,0	1.150
804 0950 004	4 x 95 SM	3.648	38,0	4.400
804 1200 001	1 x 120 RM	1.152	20,0	1.400
804 1200 004	4 x 120 SM	4.608	42,0	5.450
804 1500 001	1 x 150 RM	1.440	22,0	1.700
804 1500 004	4 x 150 SM	5.760	47,0	6.550
804 1850 001	1 x 185 RM	1.776	24,0	2.100
804 1850 004	4 x 185 SM	7.110	53,0	9.050
804 2400 001	1 x 240 RM	2.304	27,0	2.650
804 2400 004	4 x 240 SM	9.220	60,0	11.380
804 3000 001	1 x 300 RM	2.880	30,0	3.300
804 4000 001	1 x 400 RM	3.840	35,0	4.200
804 5000 001	1 x 500 RM	4.800	38,0	5.200

robust cables

Schleppflex®

BUS cables

control cables

data cables

IT/communic.

high-temp.

lift cables

rubber cables

single cores

spiral cables

accessories

technical annex